

FLOAT VALVES

FLOAT VALVES - BOB®

R1350 & R1351 SERIES BOB® FLOAT VALVES

THE R1350 & R1351 SERIES IS A HIGH CAPACITY FLOAT VALVE. THIS MODEL HAS FEMALE NPT INLET AND OUTLET CONNECTIONS. THIS MODEL IS IDEAL FOR APPLICATIONS WHERE CAUSTIC FLUIDS ARE USED OR WHERE SANITATION IS A CONCERN. FEATURES INCLUDE NSF LISTING, AN ADJUSTABLE SHORT ARM FOR CUSTOMIZING WATER LEVEL.

CONSTRUCTION: HEAVY DUTY STAINLESS STEEL CAST, AISI 316 STAINLESS STEEL COMPONENTS, STANDARD VITON® SEALS ON R1350 MODELS AND STANDARD TEFLON™ SEALS ON R1351 MODELS



R1350 Valve Only - with Disc & Cup Made of Viton®

Part Number	Pipe Size (in)		Free Discharge Flow Capacity			Weight (lbs)
	Inlet	Outlet	35 PSI	65 PSI	85 PSI	
R1350-3/8-N	3/8 NPT	3/8 NPT	37.5 GPM	52 GPM	58 GPM	1.68
R1350-1/2-N	1/2 NPT	1/2 NPT	37.5 GPM	52 GPM	58 GPM	1.63
R1350-3/4-N	3/4 NPT	3/4 NPT	37.5 GPM	52 GPM	58 GPM	1.56

R1351 Valve Only - with Disc & Cup Made of Teflon®

Part Number	Pipe Size (in)		Free Discharge Flow Capacity			Weight (lbs)
	Inlet	Outlet	35 PSI	65 PSI	85 PSI	
R1351-3/8-N	3/8 NPT	3/8 NPT	37.5 GPM	52 GPM	58 GPM	1.68
R1351-1/2-N	1/2 NPT	1/2 NPT	37.5 GPM	52 GPM	58 GPM	1.63
R1351-3/4-N	3/4 NPT	3/4 NPT	37.5 GPM	52 GPM	58 GPM	1.56

R1350-5 Valve Assembly with Stem & Float Disc & Cup Made of Viton®

Part Number	Pipe Size (in)		Float Ball	Stem (in)	Max. Inlet Pressure	Weight (lbs)
	Inlet	Outlet				
R1350-3/8-5-N	3/8 NPT	3/8 NPT	R1340-5	1/4-20 x 10	85 psi	2.69
R1350-1/2-5-N	1/2 NPT	1/2 NPT	R1340-5	1/4-20 x 10	85 psi	2.63
R1350-3/4-5-N	3/4 NPT	3/4 NPT	R1340-5	1/4-20 x 10	85 psi	2.56

R1351-5 Valve Assembly with Stem & Float Disc & Cup Made of Teflon®

Part Number	Pipe Size (in)		Float Ball	Stem (in)	Max. Inlet Pressure	Weight (lbs)
	Inlet	Outlet				
R1351-3/8-5-N	3/8 NPT	3/8 NPT	R1340-5	1/4-20 x 10	85 psi	2.69
R1351-1/2-5-N	1/2 NPT	1/2 NPT	R1340-5	1/4-20 x 10	85 psi	2.63
R1351-3/4-5-N	3/4 NPT	3/4 NPT	R1340-5	1/4-20 x 10	85 psi	2.56

Viton® is a registered trademark of DuPont-Cow Elastomers/Teflon® is a registered trademark of DuPont