

PNEUMATIC CONTROL VALVES PV926

(V926 angle valves series with linear actuators PA series)

DESCRIPTION

The PV926 control valves are single seated, two-way body constructed with angle connections. The PA pneumatic actuator is rubber diaphragm and multi-springs. It's action can be DA - direct action (air to close) or RA-reverse action (air to open). The PV926 valves have been designed to assure an accurate control in any process condition. The self draining design is ideally suited to applications in clean steam service.

MAIN FEATURES

Single seated, two way, direct or reverse action valve.
Valve top flange permanently attached to the body, removal is unnecessary for replacing the actuator.
Metal to metal or soft sealing.
Self draining design

STANDARD SURFACE FINISH

Internal parts: 0,5 microns Ra

External:

Body

Fine machined (mechanical or electro polished as option)

Actuator

Stainless steel satin bead blast finish – 1,6 microns Ra

Steel painted

OPTIONS:

Soft sealing
Position transmitter
Pneumatic pilot positioner
Air filter regulator
Top-work manual handwheel

USE:

Saturated steam
Hot and superheated water
Air and gases compatible with the construction

AVAILABLE

MODELS: PV926

VALVE SIZES: DN1/2" to DN2" ; DN15 to DN50

CONNECTIONS: Clamp ends or other on request

PNEUMATIC

ACTUATORS: PA-205,PA-280,PA-340,PA-435

ACTUATOR CONN: 1/4" NPT-F

CONTROL SIGNAL: 0,2 – 1bar; 0,4 – 1,2 bar; 0,4 – 2 bar

ELECTRIC ACT.: Consult catalogue IS EL20.00 E

HOW TO SELECT: Never size the valve according to the pipe diameter in which it has to be fitted, but according to the required actual flow of steam or water. Refer to the valve calculation data sheet or consult the factory.



MAX.AIR SUPPLY: 3,5 bar

AMBIENT

TEMPERATURE: -20°C+70°C

STEM SEALING: VITON/PTFE O-Rings 170°C

PLUG TYPES: Equal percentage (EQP)
Linear (PL)
On-Off (PT)

PORT: Full port as standard
Reduced or microflow on request

CE MARKING (PED - European Directive 97/23/EC)	
PN 16	Category
DN1/2" to DN2"	SEP - art. 3, paragraph3

MATERIALS		
POS.	DESIGNATION	MATERIAL
1	Valve Body	AISI316L / 1.4404
2	Bonnet	AISI316L / 1.4404
3	Actuator (Steel)	S235JRG2 / 1.0038
	Actuator (Stainless steel)	AISI304 / 1.4301
4	* Diaphragm	NBR 70
5	Yoke (Steel)	C45E / 1.1191
	Yoke (Stainless steel)	AISI304 / 1.4301
6	Valve Seal	PTFE
7	* Standard packing	VITON / PTFE

* Available spare parts

VALVE BODY LIM. CONDITIONS	
PRESSURE/TEMPERATURE	
16 bar	100 °C
15 bar	150 °C
14 bar	200 °C

DIMENSIONS (Clamp conn.)						
VALVE BODY				ACTUATOR		
DN	A (mm)	B (mm)	C (mm)	Type	D (mm)	ø E (mm)
1/2"-15	60	49	62,5	PA-205	235	210
3/4"-20	60	49	62,5	PA-280	240	275
1"-25	60	49	62,5	PA-340	265	335
1 1/4"-32*	60	65	67,5	PA-435	295	430
1 1/2"-40	60	65	67,5			
2"-50	60	65	67,5			

Consult factory for certified dimensions.

Dimensions subject to change without notice.

*Not available with ASME BPE

FLOW RATE COEFFICIENTS						
	SIZES					
	1/2"-15	3/4"-20	1"-25	1 1/4"-32	1 1/2"-40	2"-50
Kvs	3,8	5,1	9,4	15,4	22,2	40,1

Kvs in m³/h , see data sheet IS PV10.00 E ;

For conversion Kvs = Cv(US) x 0,855

ACTUATOR STROKE IN mm						
	SIZES					
	1/2"-15	3/4"-20	25-1"	1 1/4"-32*	1 1/2"-40	2"-50
Stroke	20	20	20	20	20	20

Connection examples		
Clamp	Round thread	Flange

