

'Apollo' Valves

SUBMITTAL SHEET

36C Series

Model PRC - Pressure Reducing Valve

Job Name:	
Job Location:	
Engineer:	
Contractor:	
Tag:	
PO Number:	
Representative:	
Wholesale Distributor:	



DESCRIPTION

The Apollo® Model PRC (36C Series) Pressure Reducing Valves are designed to protect non-potable water distribution systems by automatically controlling excessive pressure changes. The valves integral thermoplastic cage provides maximum corrosion resistance. Designed for easy in-line servicing with bottom cleanout access to seat disc and strainer.

FEATURES

- Lead Free Option Available
- Balanced Piston Design
- Sealed Spring Cage Vault
- Built-in Thermal Expansion By-Pass
- Easy Access to Seat Disc and SS Strainer
- Control Pressure Range 10-125 psi
- NPT, Solder, PEX, CPVC connections
- 100% Manufactured in USA

APPROVALS

- ASSE 1003
- CSA B356




STANDARD MATERIALS LIST

Part Name	Material
Body	Bronze, ASTM B584
Tailpiece	Brass, ASTM B16
Screen	Stainless Steel
Cap	Glass Filled Celcon®
Diaphragm	FDA grade EPDM
Seat disc	FDA grade EPDM
Stem / Adjusting Screw	Stainless Steel
Spring	Music Wire ASTM 228
O-Rings	FDA grade Nitrile

PERFORMANCE RATING

- Maximum Supply Pressure: 400 psig
- Std. Temperature Range 33°F – 180°F
- Maximum Set Pressure: 125 psig

Not intended for potable water



JUMP KIT

For use during system startup and overpressurization.

Kit Number	Size	Adapter
36C404JK	3/4"	Threaded
36C405JK	1"	Threaded
36C504JK	3/4"	Solder
36C504JKC	3/4"	CPVC
36C505JKC	1"	CPVC
36C904JK	3/4"	PEX

- Continued on Next Page -

Apollo Valves, Manufactured by **Conbraco Industries, Inc.**
 701 Matthews Mint-Hill Road, Matthews, NC 28105 USA
www.apollovalves.com | (704) 841-6000

This specification is provided for reference only. Conbraco Industries Inc. reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold. Please visit our website @ www.apollovalves.com for the most current information.




'Apollo' Valves

SUBMITTAL SHEET

36C Series

Model PRC - Pressure Reducing Valve



DIMENSIONS

Size (in.)	Connect Type	Dimensions (in.)						Wt. (Union) lbs. each
		A	B	C	D	E	F	
1/2"	THREAD	3-5/8	4-1/2	5-3/8	6	5/8	2-3/4	3.5
	SOLDER	3-5/8	4-1/2	5-1/2	6	1/2	2-3/4	3.4
	PEX	3-5/8	4-1/2	5-1/2	6	5/8	2-3/4	3.3
	CPVC	3-5/8	4-1/4	5	6	1/2	2-3/4	3.1
3/4"	THREAD	3-5/8	4-1/2	5-1/2	6	5/8	2-3/4	3.4
	SOLDER	3-5/8	4-1/2	5-1/2	6	3/4	2-3/4	3.3
	PEX	3-5/8	4-5/8	5-5/8	6	5/8	2-3/4	3.2
	CPVC	3-5/8	4-1/2	5-1/2	6	5/8	2-3/4	3
1"	THREAD	3-3/4	4-5/8	5-3/4	6	5/8	3-3/8	4.5
	SOLDER	3-3/4	4-5/8	5-3/4	6	7/8	3-3/8	4.4
	PEX	3-3/4	4-3/4	6	6	3/4	3-3/8	4.3
	CPVC	3-3/4	4-3/4	6	6	15/16	3-3/8	4

WATER CAPACITY (GPM)

Fall-Off (PSI)	Pressure Differential (PSI)		
	25	50	75
5	1.3	1.5	1.7
10	4.7	5.5	6.3
15	10.6	12.5	14.4
20	15.3	18	20.7
5	2.1	2.5	2.9
10	6.8	8	9.2
15	13.2	15.5	17.8
20	18.3	21.5	24.7
5	2.8	3.3	3.7
10	8.5	10	11.5
15	15.3	18	20.7
20	21.3	25	28.8

Nominal dimensions are shown. Allowances must be made for manufacturers' tolerances.

MODEL NUMBER

PRC	X	X	X	X	X
UNION	GAUGE	PRESSURE RANGE	SIZE	END CONNECTION*	
blank = Single Union	blank = No Gauge Port	blank = 25 - 75 PSIG	12 = 1/2"	blank = FNPT x FNPT	
E = Extended Union	P = w/Gauge Port Plugged	L = 10 - 35 PSIG	34 = 3/4"	Single Union	
D = Double Union	G = w/Pressure Gauge	H = 75 - 125 PSIG	1 = 1"	S = Solder x FNPT	
T = No Union (Threaded Only)				C = CPVC x FNPT	
				X = PEX x FNPT	
				M = Meter x FNPT	
				Double Union	
				S = Solder x Solder	
				C = CPVC x CPVC	
				X = PEX x PEX	
				B = BSPT x BSPT	
				SC = Solder x CPVC	
				SX = Solder x PEX	
				CX = CPVC x PEX	

* Also available with Press Connections. See 36C-PR Series submittal.

PART NUMBER

36C	X	XX	X	X	X
CONNECTION	SIZE	GAUGE	PRESSURE	OPTION	
1 = Single Union NPT	03 = 1/2"	0 = Without Gauge	1 = 25 - 75 PSIG range	C = CPVC Tailpiece	
2 = No Union NPT	04 = 3/4"	P = w/Gauge Port Plugged	2 = 10 - 35 PSIG range	AUB = Extended Union (3/4" and 1")	
3 = Single Union Solder x NPT	05 = 1"	G = w/Gauge	3 = 75 - 125 PSIG range		
4 = Double Union NPT					
5 = Double Union Solder					
6 = Single Union Meter					
9 = Double Union PEX					

Apollo Valves, Manufactured by **Conbraco Industries, Inc.**
 701 Matthews Mint-Hill Road, Matthews, NC 28105 USA
www.apollovalves.com | (704) 841-6000

This specification is provided for reference only. Conbraco Industries Inc. reserves the right to change any portion of this specification without notice and without incurring obligation to make such changes to Conbraco products previously or subsequently sold. Please visit our website @ www.apollovalves.com for the most current information.

